



SAFETY DATA SHEET

PRIME-A-PELL® PLUS – SERIES 662

Section 1: PRODUCT AND COMPANY IDENTIFICATION

Product Name: PRIME-A-PELL® PLUS Series 662

Product Number: C662-NOPG

Other Means of Identification

Common Name: Series 662

UN/ID no.: 1263

Synonyms: None

Recommended use of the chemical and restrictions on use:

Recommended Use: Industrial Paint

Uses Advised Against: Consumer use – For professional use only. Not for residential use.

Details of the supplier of the safety data sheet:

Manufacturer/Supplier: TEX-COTE LLC
2422 East 15th Street,
Panama City, FL 32405

Phone Number: 850-769-0347

Emergency Phone: 1-800-424-9300 (CHEMTREC)

Date of Preparation: January 10, 2026

Section 2: HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status: This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1B
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 1
Aspiration toxicity	Category 1
Flammable Liquids	Category 3

Label Elements:

EMERGENCY OVERVIEW

Danger

Hazard Statements

- Causes skin irritation
- Causes serious eye irritation
- May cause genetic defects
- May cause cancer
- May cause respiratory irritation.
- May cause drowsiness or dizziness
- Causes damage to organs through prolonged or repeated exposure
- May be fatal if swallowed and enters airways
- Flammable liquid and vapor



Appearance: Clear

Physical State: Liquid

Odor: Strong Aromatic

Precautionary Statements**Prevention:**

Obtain special instructions before use
 Do not handle until all safety precautions have been read and understood
 Use personal protective equipment as required
 Wash face, hands and any exposed skin thoroughly after handling
 Use only outdoors or in a well-ventilated area
 Do not breathe dust/fume/gas/mist/vapors/spray
 Do not eat, drink or smoke when using this product
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking
 Keep container tightly closed
 Ground/bond container and receiving equipment
 Use explosion-proof electrical/ventilating/lighting/mixing/equipment
 Use only non-sparking tools
 Take precautionary measures against static discharge
 Keep cool

Response:

IF exposed or concerned: Get medical advice/attention
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 If eye irritation persists: Get medical advice/attention
 If skin irritation occurs: Get medical advice/attention
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
 Wash contaminated clothing before reuse
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
 Do NOT induce vomiting
 In case of fire: Use CO2, dry chemical, or foam for extinction

Storage:

Store locked up
 Store in a well-ventilated place. Keep container tightly closed
 Keep away from children

Disposal:

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC):

Other information: May be harmful in contact with skin
 SEE SAFETY DATA SHEET

Acute toxicity: 0% of the mixture consists of ingredient(s) of unknown toxicity.

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	Weight-%
ALIPHATIC HYDROCARBON MIXTURE	8052-41-3	30 - <60%
ALKYLALKOXY-SILANE	18395-30-7	30 - <60%
SILICONE RESIN SOLUTION	-	1 - <10%
METHYL ALCOHOL	67-56-1	0.1 - <1%

*The exact percentage (concentration) of composition has been withheld as a trade secret.

Section 4: FIRST AID MEASURES**Description of first aid measures**

General advice: If symptoms persist, call a physician.

Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If symptoms persist, call a physician.
Skin contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If symptoms persist, call a physician.
Inhalation	Remove to fresh air. Oxygen or artificial respiration if needed.
Ingestion	If swallowed, do not induce vomiting. Get medical attention immediately.
Self-protection of the first aider	Use personal protective equipment. Avoid contact with eyes, skin, and clothing.
<u>Most important symptoms and effects, both acute and delayed</u>	
Notes to physician	Treat symptomatically.

Section 5: FIRE FIGHTING MEASURES

Suitable extinguishing media:

Foam. Dry powder. Carbon dioxide. alcohol-resistant foam.

Unsuitable extinguishing media:

Water spray.

Specific hazards arising from the chemical:

Thermal decomposition can lead to release of irritating gases and vapors In the event of fire and/or explosion do not breathe fumes.

Hazardous combustion products:

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon dioxide. Hydrocarbons. Formaldehyde.

Protective equipment and precautions for firefighters:

Use water spray to cool unopened containers. In the event of fire, wear self-contained breathing apparatus. Keep away from heat/sparks/open flames/hot surfaces. MAY CAUSE HEAT AND PRESSURE BUILD-UP IN CLOSED CONTAINERS. Solvent vapors are heavier than air and may spread along floors. Flash back possible over considerable distance.

Section 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Personal Precautions: Avoid contact with eyes, skin and clothing. Use personal protective equipment. Remove all sources of ignition.

Environmental Precautions

Environmental Precautions: Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.

Methods and Material for Containment and Cleaning Up

Methods for containment: Remove all sources of ignition. Spills may be collected with inert, absorbent material for proper disposal. Use non-sparking tools, protective gloves, goggles and clothing, adequate ventilation, avoid the breathing of vapors and use respiratory protective devices. Transfer absorbent material to suitable containers for proper disposal.

Methods for cleaning up: If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

Section 7: HANDLING AND STORAGE

Precautions for Safe Handling

Handling: Handle in accordance with good industrial hygiene and safety practice. Wear personal protective equipment. Avoid contact with eyes, skin and clothing. Remove and wash contaminated clothing before re-use. Keep away from open flames, hot surfaces and sources of ignition. Do not breathe vapors or spray mist. In case of insufficient ventilation, wear suitable respiratory equipment. Do not ingest. Ensure adequate ventilation. Do not eat, drink or smoke when using this product. Wash thoroughly after handling.

Conditions for safe storage, including any incompatibilities

Storage: Keep container tightly closed in a dry and well-ventilated place. Keep out of the reach of children.

Incompatible Products: Water. Bases. Acids. Strong oxidizing agents.

Section 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

Exposure guidelines

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
ALIPHATIC HYDROCARBON MIXTURE 8052-41-3	TWA: 100 ppm	TWA: 500 ppm TWA: 2900 mg/m ³	20000 mg/m ³
METHYL ALCOHOL 67-56-1	TWA: 200 ppm Skin STEL: 250 ppm	TWA: 200 ppm TWA: 260 mg/m ³	6000 ppm

Appropriate engineering controls

Engineering measures: Sufficient ventilation, in volume and pattern, should be provided through both local and general exhaust to keep the air contaminant concentration below current applicable OSHA Permissible Exposure Limits (PEL) and ACGIH's Threshold Limit Values (TLV). Appropriate ventilation should be employed to remove hazardous decomposition products formed during welding or flame cutting operations of surfaces coated with this product.

Individual protection measures, such as personal protective equipment

Eye/face protection: Use chemical resistant splash type goggles. If splashes are likely to occur, wear face-shield.

Skin and body protection: Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

Respiratory protection: Use only with adequate ventilation. Do not breathe vapors, spray mist, or dust. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist or dust levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use.

General hygiene considerations: Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical State	liquid	Odor	Strong Aromatic
Appearance	Clear	Odor Threshold	No information available
Color	No information available		

Property	Values	Remarks
pH		No data available
Melting Point / Freezing Point	No data available	No data available
Boiling Point / Boiling Range		No information available
Flash Point	29 °C / 85.0 °F	Pensky Martens - Closed Cup
Evaporation Rate		No data available
Flammability (solid/gas)	No data available	Not applicable
Flammability Limit in Air		No data available
Upper Flammability limit	N/A	
Lower Flammability limit	N/A	
Vapor Pressure		No data available
Vapor Density		No data available
Specific Gravity	.83048	g/cm ³
Water Solubility	Insoluble in cold water	
Solubility in Other Solvents		No data available
Partition Coefficient: n-octanol/water		No data available
Autoignition Temperature	No data available	No data available
Decomposition Temperature	No information available	No data available
Kinematic Viscosity	No information available	No data available
Dynamic Viscosity		No data available

Other Information		
Molecular Weight	No information available	
Density	6.91083 lbs/gal	
Volatile Organic Compounds (VOC) Content	4.964 lbs/gal	
Total Volatiles Weight Percent	71.8259 %	
Total Volatiles volume percent	77.6623 %	
Bulk Density	No information available	

Section 10: STABILITY AND REACTIVITY

Reactivity:	Water reactive.
Chemical stability:	Stable under recommended storage conditions.
Possibility of hazardous reactions:	None under normal processing.
Conditions to avoid:	Heat, flames and sparks. Exposure to air or moisture over prolonged periods.
Incompatible materials:	Water, Bases, Acids, Strong oxidizing agents.
Hazardous decomposition products:	Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon dioxide. Hydrocarbons. Formaldehyde.

Section 11: TOXICOLOGY INFORMATION

Information on Likely Routes of Exposure

Inhalation:	May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination.
Eye contact:	Severely irritating to eyes.
Skin contact:	Irritating to skin.
Ingestion:	Potential for aspiration if swallowed. Aspiration may cause pulmonary edema and pneumonitis. May be fatal if swallowed and enters airways.

Information on toxicological effects

Symptoms Irritating to eyes and skin. May cause respiratory irritation.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Chronic Toxicity:	Avoid repeated exposure. Prolonged exposure may cause chronic effects. May cause cancer. May cause genetic defects. Causes damage to organs through prolonged or repeated exposure.
Sensitization:	No information available
Mutagenicity:	May cause genetic defects
Carcinogenicity:	The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
ALIPHATIC HYDROCARBON MIXTURE 8052-41-3	.	-	-	

Reproductive Effects	No information available.
STOT – Single Exposure	Causes damage to organs
STOT – Repeated Exposure	Causes damage to organs through prolonged or repeated exposure
Aspiration Hazard	Risk of serious damage to the lungs (by aspiration).
Acute Toxicity	0 % of the mixture consists of ingredient(s) of unknown toxicity.

Section 12: ECOLOGICAL INFORMATION

Ecotoxicity

92.4184 % of the mixture consists of component(s) of unknown hazards to the aquatic environment.

Chemical name	Toxicity to algae	Toxicity to fish	Toxicity to daphnia
METHYL ALCOHOL 67-56-1	-	LC50: 28200 mg/L Pimephales promelas 96 h flow-through LC50: >100 mg/L Pimephales promelas 96 h static LC50: 19500 - 20700 mg/L Oncorhynchus mykiss 96 h flow-through LC50: 18 - 20 mL/L Oncorhynchus mykiss 96 h static LC50: 13500 - 17600 mg/L Lepomis macrochirus 96 h flow-through	-

Persistence and Degradability

No information available

Bioaccumulation

No information available

Mobility in Environmental Media

Chemical name	log Pow
ALIPHATIC HYDROCARBON MIXTURE 8052-41-3	6.4
METHYL ALCOHOL 67-56-1	-0.77

Other Adverse Effects

No information available

Section 13: DISPOSAL CONSIDERATIONS

Waste Treatment Methods

Disposal Methods: Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

Contaminated packaging: Empty containers should be taken to an approved waste handling site for recycling or disposal.

US EPA Waste Number

Chemical Name	RCRA	RCRA – Basis for Listing	RCRA – D Series Wastes	RCRA – U Series Wastes
METHYL ALCOHOL 67-56-1		Included in waste stream: F039		U154
METHYL ALCOHOL		Included in waste stream: F039		U154

California Hazardous Waste Status

Chemical name	CAWAST
METHYL ALCOHOL 67-56-1	Toxic Ignitable

Section 14: TRANSPORTATION INFORMATION

DOT

UN/ID no.: 1263
 Proper Shipping Name: Paint related material
 Hazard Class: 3
 Packing Group: III
 Emergency Response Guide Number: 128
 ERG Code: 366
 Additional Information: For additional information, contact Tex-Cote at 800-454-0340 or info@texcote.com.

Section 15: REGULATORY INFORMATION

International Inventories

TSCA	Complies
DSL / NDSL	Complies
EINECS/ELINCS	Complies
ENCS	Does Not Comply
IECSC	Complies
KECL	Does Not Comply
PICCS	Complies
AICS	Complies

TSCA – United States Toxic Substances Control Act Section 8(b) Inventory

DSL / NDSL – Canadian Domestic Substances List/Non-Domestic Substances List

EINECS / ELINCS – European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

ENCS – Japan Existing and New Chemical Substances

IECSC – China Inventory of Existing Chemical Substances

KECL – Korean Existing and Evaluated Chemical Substances

PICCS – Philippines Inventory of Chemicals and Chemical Substances

AICS – Australian Inventory of Chemical Substances

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 12 (40 CFR 61).

Chemical Name: METHYL ALCOHOL

HAPS Data

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	SARA 313 - Threshold Values
METHYL ALCOHOL - 67-56-1	1.0

SARA 311/312 HazardousCategorization

Acute Health Hazard: Yes

Chronic Health Hazard: Yes

Fire Hazard: Yes

Sudden Release of Pressure Hazard: No

Reactive Hazard: No

CERCLA

Chemical Name	Hazardous Substances RQs	CERCLA EHS RQs	RQ
METHYL ALCOHOL 67-56-1	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

California Prop. 65

WARNING: This product can expose you to the following chemicals which are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Chemical Name	California Prop. 65
ALIPHATIC HYDROCARBON MIXTURE - 8052-41-3	.
METHYL ALCOHOL - 67-56-1	Developmental

California SCAQMD Rule 443

Contains Photochemically Reactive Solvent

State Right-to-Know

Chemical Name	New Jersey	Massachusetts	Pennsylvania
ALIPHATIC HYDROCARBON MIXTURE 8052-41-3	X	X	X
METHYL ALCOHOL 67-56-1	X	X	X

Section 16: OTHER INFORMATION

NFPA	Health 2	Flammability 3	Instability 1	Physical Hazard *
HMIS (Hazardous Material Information System)	Health 2*	Flammability 3	Reactivity 1	

Prepared By Tnemec Regulatory Dept: 816-474-3400

Revision Date 03-May-2024

Revision Summary

9 8 11 14 15 1 7 13

Disclaimer:

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.