



SAFETY DATA SHEET

PRIME-A-PELL® 200 - SERIES 660

Section 1: PRODUCT AND COMPANY IDENTIFICATION

Product Name: PRIME-A-PELL® 200 Series 660

Product Number: C660-NOPG

Other Means of Identification

Common Name: Series 660

Synonyms: None

Recommended use of the chemical and restrictions on use

Recommended Use: Industrial Paint

Uses Advised Against: Consumer use - For professional use only. Not for residential use.

Details of the supplier of the safety data sheet

Manufacturer/Supplier: TEX-COTE LLC
2422 East 15th Street,
Panama City, FL 32405

Phone Number: 850-769-0347

Emergency Phone: 1-800-424-9300 (CHEMTREC)

Date of Preparation: January 7, 2026

Section 2: HAZARDS IDENTIFICATION

Classification

OSHA/HCS Status: This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1B
Specific target organ toxicity (repeated exposure)	Category 1
Aspiration toxicity	Category 1
Flammable Liquids	Category 3

Label Elements

EMERGENCY OVERVIEW

Danger

Hazard Statements

May cause genetic defects
May cause cancer
Causes damage to organs through prolonged or repeated exposure
May be fatal if swallowed and enters airways
Flammable liquid and vapor



Appearance: Clear

Physical State: Liquid

Odor: Strong Aromatic

Precautionary Statements**Prevention:**

Obtain special instructions before use
 Do not handle until all safety precautions have been read and understood
 Use personal protective equipment as required
 Do not breathe dust/fume/gas/mist/vapors/spray
 Wash face, hands and any exposed skin thoroughly after handling
 Do not eat, drink or smoke when using this product
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking
 Keep container tightly closed
 Ground/bond container and receiving equipment
 Use explosion-proof electrical/ventilating/lighting/mixing/equipment
 Use only non-sparking tools
 Take precautionary measures against static discharge

Response:

IF exposed or concerned: Get medical advice/attention
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
 Do NOT induce vomiting
 In case of fire: Use CO₂, dry chemical, or foam for extinction

Storage:

Store locked up
 Store in a well-ventilated place. Keep cool
 Keep away from children

Disposal:

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC):

May cause skin and eye irritation.

Other information:

May be harmful in contact with skin
 SEE SAFETY DATA SHEET

Acute toxicity: 0% of the mixture consists of ingredient(s) of unknown toxicity.

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	Weight-%
ALIPHATIC HYDROCARBON MIXTURE	8052-41-3	60 - 100%
SILICONE RESIN SOLUTION	-	1 - <10%

*The exact percentage (concentration) of composition has been withheld as a trade secret.

Section 4: FIRST AID MEASURES**Description of first aid measures**

General advice: If symptoms persist, call a physician.
Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If symptoms persist, call a physician.
Skin contact Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If symptoms persist, call a physician.

Inhalation	Remove to fresh air. Oxygen or artificial respiration if needed.
Ingestion	If swallowed, do not induce vomiting. Get medical attention immediately.
Self-protection of the first aider	Use personal protective equipment. Avoid contact with eyes, skin and clothing.

Most important symptoms and effects, both acute and delayed.

Notes to physician Treat symptomatically.

Section 5: FIRE FIGHTING MEASURES

Suitable extinguishing media:

Foam. Dry powder. Carbon dioxide. alcohol-resistant foam.

Unsuitable extinguishing media:

Water spray.

Specific hazards arising from the chemical:

Thermal decomposition can lead to release of irritating gases and vapors In the event of fire and/or explosion do not breathe fumes.

Hazardous combustion products: Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon dioxide. Hydrocarbons. Formaldehyde.

Protective equipment and precautions for firefighters:

Use water spray to cool unopened containers. In the event of fire, wear self-contained breathing apparatus. Keep away from heat/sparks/open flames/hot surfaces. MAY CAUSE HEAT AND PRESSURE BUILD-UP IN CLOSED CONTAINERS. Solvent vapors are heavier than air and may spread along floors. Flash back possible over considerable distance.

Section 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Personal precautions: Avoid contact with eyes, skin and clothing. Use personal protective equipment. Remove all sources of ignition.

Environmental Precautions

Environmental precautions: Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.

Methods and Material for Containment and Cleaning Up

Methods for containment: Remove all sources of ignition. Spills may be collected with inert, absorbent material for proper disposal. Use non-sparking tools, protective gloves, goggles and clothing, adequate ventilation, avoid the breathing of vapors and use respiratory protective devices. Transfer absorbent material to suitable containers for proper disposal.

Methods for cleaning up: If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

Section 7: HANDLING AND STORAGE

Precautions for Safe Handling

Handling: Handle in accordance with good industrial hygiene and safety practice. Wear personal protective equipment. Avoid contact with eyes, skin and clothing. Remove and wash contaminated clothing before re-use. Keep away from open flames, hot surfaces and sources of ignition. Do not breathe vapors or spray mist. In case of insufficient ventilation, wear suitable respiratory equipment. Do not ingest. Ensure adequate ventilation. Do not eat, drink or smoke when using this product. Wash thoroughly after handling.

Conditions for safe storage, including any incompatibilities

Storage: Keep container tightly closed in a dry and well-ventilated place. Keep out of the reach of children.

Incompatible Products: Water. Bases. Acids. Strong oxidizing agents.

Section 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters
Exposure guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
ALIPHATIC HYDROCARBON MIXTURE 8052-41-3	TWA: 100 ppm	TWA: 500 ppm TWA: 2900 mg/m ³	20000 mg/m ³

Appropriate engineering controls

Engineering measures: Sufficient ventilation, in volume and pattern, should be provided through both local and general exhaust to keep the air contaminant concentration below current applicable OSHA Permissible Exposure Limits (PEL) and ACGIH's Threshold Limit Values (TLV). Appropriate ventilation should be employed to remove hazardous decomposition products formed during welding or flame cutting operations of surfaces coated with this product.

Individual protection measures, such as personal protective equipment

Eye/face protection: Safety glasses with side-shields if splashes are likely to occur, wear face-shield.

Skin and body protection: Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

Respiratory protection: Use only with adequate ventilation. Do not breathe vapors, spray mist, or dust. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist or dust levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use.

General hygiene considerations: Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical State	Liquid	Odor	Strong Aromatic
Appearance	Clear	Odor Threshold	No information available
Color	No information available		

Property	Values	Remarks
pH		
Melting Point / Freezing Point	No data available	
Boiling Point / Boiling Range	154 °C / 310.0 °F	
Flash Point	38 °C / 100.0 °F	
Evaporation Rate		Pensky Martens - Closed Cup
Flammability (solid/gas)	No data available	
Flammability Limit in Air		
Upper Flammability limit	N/A	
Lower Flammability limit	N/A	
Vapor Pressure		
Vapor Density		
Specific Gravity	.77954	g/cm ³
Water Solubility	Insoluble in cold water	
Solubility in Other Solvents		
Partition Coefficient: n-octanol/water		
Autoignition Temperature	No data available	
Decomposition Temperature	No information available	
Kinematic Viscosity	No information available	
Dynamic Viscosity		
Explosive Properties	No information available	
Oxidizing Properties	No information available	

Other Information		
Molecular Weight	No information available	
Density	6.48693 lbs/gal	
Volatile Organic Compounds (VOC) Content	6.070 lbs/gal	
Total Volatiles Weight Percent	93.5760 %	
Total Volatiles volume percent	95.5606 %	
Bulk Density	No information available	

Section 10: STABILITY AND REACTIVITY

Reactivity: Water Reactive

Chemical stability: Stable under recommended storage conditions.

Possibility of hazardous reactions: None under normal processing.

Conditions to avoid: Heat, flames and sparks. Exposure to air or moisture over prolonged periods.

Incompatible materials: Water, Bases, Acids, Strong oxidizing agents

Hazardous decomposition products: Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon dioxide. Hydrocarbons. Formaldehyde.

Section 11: TOXICOLOGY INFORMATION

Information on likely routes of exposure

Inhalation: May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination.

Eye contact: May cause temporary eye irritation.

Skin contact: Prolonged contact may cause redness and irritation.

Ingestion: Potential for aspiration if swallowed. Aspiration may cause pulmonary edema and pneumonitis. May be fatal if swallowed and enters airways.

Information on toxicological Effects

Symptoms: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Skin disorders.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Chronic Toxicity: NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Avoid repeated exposure. Substances known to be mutagenic to man. Substances known to be carcinogenic to man. Causes damage to organs through prolonged or repeated exposure.

Sensitization: No information available.

Mutagenicity: May cause genetic defects.

Carcinogenicity: The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
ALIPHATIC HYDROCARBON MIXTURE 8052-41-3	.	-	-	

Reproductive effects: No information available.

STOT - single exposure: No information available.

STOT - repeated exposure: Causes damage to organs through prolonged or repeated exposure

Aspiration hazard: Risk of serious damage to the lungs (by aspiration).

Acute Toxicity: 0 % of the mixture consists of ingredient(s) of unknown toxicity.

Section 12: ECOLOGICAL INFORMATION

Ecotoxicity: 92.4184 % of the mixture consists of component(s) of unknown hazards to the aquatic environment.

Persistence and degradability: No information available.

Bioaccumulation: No information available.

Mobility in Environmental Media

Chemical Name	log Pow
ALIPHATIC HYDROCARBON MIXTURE 8052-41-3	6.4

Other Adverse Effects: No information available.

Section 13: DISPOSAL CONSIDERATIONS

Waste Treatment Methods

Disposal Methods: Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

Contaminated packaging: Empty containers should be taken to an approved waste handling site for recycling or disposal.

US EPA Waste Number

Chemical Name	RCRA	RCRA – Basis for Listing	RCRA – D Series Wastes	RCRA – U Series Wastes
METHYL ALCOHOL		Included in waste stream: F039		U154

Section 14: TRANSPORTATION INFORMATION

DOT

Proper Shipping Name: paint in oil

Additional Information For additional information, contact Tex-Cote at 800-454-0340 or info@texcote.com.

Section 15: REGULATORY INFORMATION

International Inventories

TSCA	Complies
DSL / NDSL	Complies
EINECS/ELINCS	Complies
ENCS	Does Not Comply
IECSC	Complies
KECL	Complies
PICCS	Complies
AICS	Complies

TSCA – United States Toxic Substances Control Act Section 8(b) Inventory

DSL / NDSL – Canadian Domestic Substances List/Non-Domestic Substances List

EINECS / ELINCS – European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

ENCS – Japan Existing and New Chemical Substances

IECSC – China Inventory of Existing Chemical Substances

KECL – Korean Existing and Evaluated Chemical Substances

PICCS – Philippines Inventory of Chemicals and Chemical Substances

AICS – Australian Inventory of Chemical Substances

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 12 (40 CFR 61).

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazardous**Categorization****Acute Health Hazard:** Yes**Chronic Health Hazard:** Yes**Fire Hazard:** Yes**Sudden Release of Pressure Hazard:** No**Reactive Hazard:** No**California Prop. 65****WARNING:** This product can expose you to the following chemicals which are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Chemical Name	California Prop. 65
ALIPHATIC HYDROCARBON MIXTURE - 8052-41-3	
METHYL ALCOHOL	Developmental

California SCAQMD Rule 443

Contains Photochemically Reactive Solvent

State Right-to-Know

Chemical Name	New Jersey	Massachusetts	Pennsylvania
ALIPHATIC HYDROCARBON MIXTURE 8052-41-3	X	X	X

Section 16: OTHER INFORMATION

NFPA	Health 2	Flammability 2	Instability 1	Physical Hazard *
HMIS (Hazardous Material Information System)	Health 2*	Flammability 2	Reactivity 1	

Prepared By Tnemec Regulatory Dept: 816-474-3400**Revision Date** 06-FEB-2024**Revision Summary**

9 4 5 7 8 10 11 14 15 113

Disclaimer:

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.